

Continental Arctic LCP3

Arctic® LCP3

Arctic® LCP3 is made for high-pressure service with tight bends for petroleum- and water-based hydraulic fluids.

Performance + Specs

Meets or exceeds the performance requirements of

- SAE 100R17

Meets Flame Resistance

- USMSHA Designation

Inner Tube

Nitrile (NBR) Black

Reinforcement

One braid of high-tensile steel wire.

Cover

CR (Polychloroprene) Black

Temperature Range

-70°F / -57°C ~ 212°F / 100°C

Key Features

1/2 Bend Radius

4:1 Safety Factor

Low Temperature Rating

Branding

Continental ARCTIC® LCP3-08 SAE 100R17; DN12 1/2" 3250 PSI 22.4 MPa 224 BAR MSHA 2G-IC-14C/41 MADE IN USA

Arctic® LCP3

Product Numbers

SAP	Product #	ID	ID		OD		Max Working Pressure		Bend Radius	
		Fraction	in.	mm.	in.	mm.	PSI	MPa	in.	mm.
21067732	LCP3-04X250RL	1/4	0.25	6.4	0.38	9.65	3250	22.41	1.50	38.1
21067739	LCP3-06X250RL	3/8	0.38	9.7	0.50	12.7	3250	22.41	2.00	50.8
21067784	LCP3-08X250RL	1/2	0.50	12.7	0.79	20.1	3250	22.41	2.80	71.1

No Fittings Found