

X-Life™ XCP3

X-LIFE™XCP3 is for high-pressure hydraulic applications needing abrasion resistance. This hose is designed for use where higher pressures and a more flexible hose are required.

Performance + Specs

Meets or exceeds the performance requirements of

- 100R17 & ISO 18752

Meets Flame Resistance

- **USMSHA Designation**

Smooth Cover

Inner Tube

Nitrile (NBR) Black

Reinforcement

(1) Braid of High-Tensile Steel Wire (2) Wire Braid; Sizes 5/8", 3/4 & 1"

Cover

Synthetic Rubber Black

Temperature Range

-40°F / -40°C ~ 212°F / 100°C

Key Features

4:1 Safety Factor

Extended Life™ Cover

Handles Constant Pressure

SAE J1942/ U.S. Coast Guard

Branding

X-Life™ XCP3-08 SAE 100R17 / ISO 18752 1/2" (DN12) 3250 PSI 22.4 MPa MSHA 2G-1C-14C/37 MADE IN USA

X-Life™ XCP3

Product Numbers

SAP	Product #	ID	ID		OD		Max Working Pressure		Bend Radius		MIN BURST Pressure		Fitting Type	Weight (lb/ft)
		Fraction	in.	mm.	in.	mm.	PSI	MPa	in.	mm.	PSI	Mpa		
20738196	XCP3-04	1/4	0.25	6.40	0.50	12.70	3250	22.41	1.50	38.00	13000	90.00	B2	0.11
20784065	XCP3-06	3/8	0.38	9.50	0.65	16.50	3250	22.41	2.00	51.00	13000	90.00	B2	0.17
20774712	XCP3-08	1/2	0.50	12.70	0.78	19.80	3250	22.41	2.80	71.00	13000	90.00	B2	0.28
20777228	XCP3-10	5/8	0.63	15.90	0.95	24.10	3250	22.41	3.00	76.00	13000	90.00	B2	0.41
20777501	XCP3-12	3/4	0.75	19.00	1.13	28.70	3250	22.41	3.80	97.00	13000	90.00	B2	0.55
20774714	XCP3-16	1	1.00	25.40	1.44	36.60	3250	22.41	4.50	114.00	13000	90.00	B2	0.82