

AG SPRAY

Continental AG Spray is a lightweight, economical high-pressure hose for carrying air, water and many spray solutions in agricultural applications: including Xylene up to 10% concentration.

Performance + Specs

Tube

- PVC Compound
- ARPM Class B (Good Oil Resistance)

Cover

- PVC Compound
- ARPM Class B (Good Oil Resistance)
- Ribbed Finish

Reinforcement

- Spiral Synthetic Yarn

Temperature Range

- 0°F / -18°C ~ 158°F / 70°C

Design Factor

- 3:1

Packaging

- Reels
- Coiled & Poly-Wrapped

Coupling

- Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

Non Stock / Sizes

- For special production run minimum requirements, Contact Customer Service.

Branding

AG SPRAY 1800 1/2" (12.7 mm) 3:1 D.F. Made in USA

AG Spray

Order Codes: 540-211 (Orange)

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
3/8	9.50	0.69	17.50	300	Orange	1800	12.41	600	4.14	0.15	0.22	20012638
1/2	12.70	0.83	21.20	300	Orange	1800	12.41	600	4.14	0.20	0.29	20012641
3/4	19.05	1.10	28.00	300	Orange	1800	12.41	600	4.14	0.27	0.40	20012643