



ARVAC SW

Heavy-duty abrasion-resistant suction hose used for a variety of abrasive material-handling applications, including the transfer of sand, gravel, cement, fly ash, glass, metals, plastic pellets, fertilizers, rock salts and slurries. Static wire for static dissipation.

Performance + Specs

Tube Thermoplastic Polyurethane	Cover PVC / Nitrile Blend
Reinforcement - Rigid High-Density PVC Helix - with Static Wire	Temperature Range -40°F / -40°C ~ 158°F / 70°C
Design Factor 3:1	Packaging - 1-1/4" to 6" – 20ft Lengths, Polytube -100ft Lengths, Coiled & Poly-Wrapped - 8" to 10" - 20ft, 40ft and 50ft Lengths, Polytube
Coupling Contact fitting manufacturer for proper fitting recommendation and coupling procedure.	Non Stock / Sizes Contact Continental for special production run minimum requirements.

Branding

Not branded

Arvac SW

Order Codes: 586-550

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	Bend Radius (in.)	Bend Radius (mm)	Vacuum (in.)	Vacuum (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1-1/2	38.10	1.87	47.40	100	Black	160	1.10	3.00	76.20	29.00	736.60	40	0.28	0.35	0.52	20448194
2	50.80	2.47	62.80	100	Black	160	1.10	3.00	76.20	29.00	736.60	40	0.28	0.53	0.79	20448193
2-1/2	63.50	3.03	76.90	100	Black	140	0.97	4.00	101.60	29.00	736.60	35	0.24	0.79	1.17	20448192
3	76.20	3.59	91.20	100	Black	120	0.83	6.00	152.40	29.00	736.60	30	0.21	1.09	1.62	20448191
4	101.60	4.69	119.20	100	Black	120	0.83	7.00	177.80	29.00	736.60	30	0.21	1.52	2.26	20448190
5	127.00	5.81	147.50	100	Black	120	0.83	8.00	203.20	29.00	736.60	25	0.17	2.56	3.81	20447689
6	152.40	7.00	177.80	20	Black	100	0.69	8.00	203.20	29.00	736.60	25	0.17	3.67	5.47	20452698
				100	Black	100	0.69	8.00	203.20	29.00	736.60	25	0.17	3.67	5.47	20447688
8	203.20	9.13	232.00	20	Black	80	0.55	18.00	457.20	29.00	736.60	20	0.14	5.57	8.28	20447687
				50	Black	80	0.55	18.00	457.20	29.00	736.60	20	0.14	5.57	8.28	20450354
10	254.00	11.16	283.50	20	Black	80	0.55	36.00	914.40	29.00	736.60	20	0.14	7.49	11.14	20447686